

SAJ










SAJ

R5 Series Residential Solar Inverter

R5-3K/3.6K/4K/5K/6K/7K/8K-S2



SAJ

-  Lightning protection
High precision leakage monitoring
-  Die-casting case cover
Beautiful & reliable
-  Low standby consumption
High efficiency, high yield
-  APP connection
All data at real time
-  Remote Maintenance
Remote Configuration
-  Quiet generation
No noise pollution
-  Intelligent & Grid-friendly
Active response to grid dispatch

GUANGZHOU SANJING ELECTRIC CO., LTD.

Website: www.saj-electric.com

E-mail: info@saj-electric.com

Add: SAJ Innovation Park, No.9, Lizhishan Road, Science City, Guangzhou, Guangdong, P.R.China.



Technical Data

R5-3K/3.6K/4K/5K/6K/7K/8K-S2

Type	R5-3K-S2	R5-3.6K-S2	R5-4K-S2	R5-5K-S2	R5-6K-S2	R5-7K-S2	R5-8K-S2
Input (DC)							
Max.PV Array Power [Wp]@STC	4500	5400	6000	7500	9000	10500	12000
Max. DC Voltag [V]				600			
MPPT Voltage Range [V]				90-550			
Nominal DC Voltage[V]				360			
Start Voltage [V]				100			
Min. DC Voltage [V]				80			
Max. DC Input Current [A]			12.5/12.5				25/12.5
Number of DC Connection Sets per MPPT			1/1				2/1
Number of MPPT				2			
DC Switch				Integrated			
Output (AC)							
Rated AC Power [W]	3000	3680	4000	5000*1	6000	7000	8000
Max. AC Power*2 [VA]	3300	3680	4400	5500	6000	7700	8000
Rated AC Current [A]@230Vac	13.1	16.0	17.4	21.8*3	26.1	30.5	34.8
Max. AC Current [A]	14.4	16.0	19.2	24.0	26.1	33.5	34.8
Nominal AC Voltage/ Range [V]				220,230,240/180-280			
Grid Frequency/ Range [Hz]				50,60/45-55,55-65			
Power Factor [cos φ]				0.8 leading~0.8 lagging			
Total Harmonic Distortion [THDi]				< 2%(at nominal power)			
Feed-in				L+N+PE			
Efficiency							
Max. Efficiency	97.8%	98.0%	98.0%	98.1%	98.2%	98.2%	98.3%
Euro Efficiency	97.2%	97.5%	97.5%	97.6%	97.6%	97.7%	97.8%
MPPT Accuracy				>99.9%			
Protection							
Internal Over-voltage Protection				Integrated			
DC Insulation Monitoring				Integrated			
DC Surge Protection				Integrated			
Grid Monitoring				Integrated			
AC Short Circuit Current Protection				Integrated			
AC Grounding Detection				Integrated			
GFCI Monitoring				Integrated			
DCI Monitoring				Integrated			
AC Surge Protection				Integrated			
Thermal Protection				Integrated			
Anti-island protection monitoring				AFD			
Interface							
DC Connection				MC4			
AC Connection			Plug-in connector				Terminal Block
Human Machine Interface				LED + (bluetooth/Wi-Fi+APP)			
Communication Port				RS232(USB joints)+RS485(RJ45 crystal joints)			
Communication Mode				Wi-Fi / GPRS / 4G(Optional)			
General Data							
Topology				Transformerless			
Consumption at Night [W]				<0.2			
Consumption at Standby [W]				6			
Operating Temperature Range			-40°C to +60°C (running in reduced load condition when the temperature is above 45°C)				
Cooling Method				Natural Convection			
Ambient Humidity				0-100% Non-condensing			
Altitude				4000m (>3000m power derating)			
Noise [dBA]				<25			
Ingress Protection				IP65			
Mounting				Rear Panel			
Dimensions [H*W*D][mm]			389*367*143				429*418*177
Weight [kg]			12.2				18
Standard Warranty [Year]				5 (standard)/10/15/20/25 (Optional)			
Applicable Standard			IEC62109-1/2, IEC61000-6-1/2/3/4, EN50438, C10/C11, IEC62116, IEC61727, RD1699, UNE 206006, UNE 206007, CEI 0-21, AS4777.2, CQC NB/T 32004-2013, VDE-AR-N 4105				

Remarks:

*1 According to VDE - ARN - N 4105, Rated AC Power for R5-5K-S2 is 4600VA; According to AS4777, Rated AC Power for R5-5K-S2 is 4999VA. *2 According to C10/C11, Max. AC Power = Rated AC Power *3 According to VDE - ARN - N 4105, Rated AC Current for R5-5K-S2 is 20A; According to AS4777, Rated AC Current for R5-5K-S2 is 21.7A.